Company API

This document explains the available methods and request/response formats for the IP->Company API

Endpoint:

`https://api.funnelfuel.io`

Authentication header:

`x-api-key: <YOUR API KEY>`

Endpoints:

GET /company

REQUEST

Query Parameters:

key	value	required
ip	Valid IPv4 address	yes

Example:

`?ip=192.168.0.1`

RESPONSE

JSON body:

key	value	required	default
domain	Domain of company	no	n/a
company	Company trade name	no	null
country	Country where company is based	no	null

isISP	Whether or not IP belongs to an ISP	yes	False

Example:

```
# If IP belongs to company
{
  "domain": "example.com",
  "company": "Example INC.",
  "country": null,
  "isISP": False
}

# If IP does NOT belong to a company
{
  "isISP": True
}
```

POST /company

REQUEST

Post body JSON:

key	value	required
ips	Array of valid IPv4 addresses	yes

Example:

```
{
  "ips": [
    "127.0.0.1",
    "192.168.0.1"
  ]
}
```

RESPONSE

JSON body:

key	value
provided IP address	Company Object

Company Object:

key	value	required	default
domain	Domain of company	no	n/a
company	Company trade name	no	null
country	Country where company is based	no	null
isISP	Whether or not IP belongs to an ISP	yes	False

Example:

```
{
  "192.168.0.1": {
      # If IP belongs to company
      "domain": "example.com",
      "company": "Example INC.",
      "country": null,
      "isISP": False
    },
  "127.0.0.1": {
    # If IP does NOT belong to a company
    "isISP": True
  }
}
```

Revision #2
Created 16 April 2024 20:15:05 by Ben Dzamba
Updated 18 April 2024 02:52:57 by Ben Dzamba